

# Structured Polynomial Optimization: A Unified Approach for Global Optimization

王杰

中国科学院数学与系统科学研究院

全国代数会议, 泉州, 2023 年 11 月 17 日



# Outline

- 1 Polynomial optimization and the Moment-SOS hierarchy
- 2 Structures in polynomial optimization
- 3 Numerical examples and applications

# Outline

- ① Polynomial optimization and the Moment-SOS hierarchy
- ② Structures in polynomial optimization
- ③ Numerical examples and applications

# Outline

- ① Polynomial optimization and the Moment-SOS hierarchy
- ② Structures in polynomial optimization
- ③ Numerical examples and applications

# Polynomial optimization

- Polynomial optimization problem (POP):

$$f_{\min} := \begin{cases} \inf_{\mathbf{x} \in \mathbb{R}^n} & f(\mathbf{x}) \\ \text{s.t.} & g_i(\mathbf{x}) \geq 0, \quad i = 1, \dots, m \end{cases}$$

- non-convex, NP-hard
- power systems, computer vision, combinatorial optimization, neural networks, signal processing, quantum information...

# Polynomial optimization

- Polynomial optimization problem (POP):

$$f_{\min} := \begin{cases} \inf_{\mathbf{x} \in \mathbb{R}^n} & f(\mathbf{x}) \\ \text{s.t.} & g_i(\mathbf{x}) \geq 0, \quad i = 1, \dots, m \end{cases}$$

- non-convex, NP-hard
- power systems, computer vision, combinatorial optimization, neural networks, signal processing, quantum information...

# Polynomial optimization

- Polynomial optimization problem (POP):

$$f_{\min} := \begin{cases} \inf_{\mathbf{x} \in \mathbb{R}^n} & f(\mathbf{x}) \\ \text{s.t.} & g_i(\mathbf{x}) \geq 0, \quad i = 1, \dots, m \end{cases}$$

- non-convex, NP-hard
- power systems, computer vision, combinatorial optimization, neural networks, signal processing, quantum information...

# Why polynomial optimization?

- closely related to real algebraic geometry: the theory of positive polynomials, convex algebraic geometry
- be able to compute the globally optimal value/solutions: the Moment-SOS hierarchy
- closely related to theoretical computer science: the theory of approximation algorithms, the theory of complexity
- Powerful modelling ability: QCQP, binary program, (mixed) integer (non-)linear program and so on

# Why polynomial optimization?

- closely related to real algebraic geometry: the theory of positive polynomials, convex algebraic geometry
- be able to compute the globally optimal value/solutions: the Moment-SOS hierarchy
- closely related to theoretical computer science: the theory of approximation algorithms, the theory of complexity
- Powerful modelling ability: QCQP, binary program, (mixed) integer (non-)linear program and so on


# Why polynomial optimization?

- closely related to real algebraic geometry: the theory of positive polynomials, convex algebraic geometry
- be able to compute the globally optimal value/solutions: the Moment-SOS hierarchy
- closely related to theoretical computer science: the theory of approximation algorithms, the theory of complexity
- Powerful modelling ability: QCQP, binary program, (mixed) integer (non-)linear program and so on

# Why polynomial optimization?

- closely related to real algebraic geometry: the theory of positive polynomials, convex algebraic geometry
- be able to compute the globally optimal value/solutions: the Moment-SOS hierarchy
- closely related to theoretical computer science: the theory of approximation algorithms, the theory of complexity
- Powerful modelling ability: QCQP, binary program, (mixed) integer (non-)linear program and so on

# Non-convexity of polynomial optimization



# Example (moment relaxation)

$$\begin{array}{ll} \inf_x & x_1^2 + x_1 x_2 + x_2^2 \\ \text{s.t.} & 1 - x_1^2 \geq 0, 1 - x_2^2 \geq 0 \end{array} \quad \iff \quad \begin{cases} \inf_x & x_1^2 + x_1 x_2 + x_2^2 \\ \text{s.t.} & \begin{bmatrix} 1 & x_1 & x_2 \\ x_1 & x_1^2 & x_1 x_2 \\ x_2 & x_1 x_2 & x_2^2 \end{bmatrix} = [1, x_1, x_2] \cdot [1, x_1, x_2]^T \succeq 0, \\ & 1 - x_1^2 \geq 0, 1 - x_2^2 \geq 0 \end{cases}$$

$$\iff \begin{cases} \inf_y & y_{2,0} + y_{1,1} + y_{0,2} \\ \text{s.t.} & \begin{bmatrix} 1 & y_{1,0} & y_{0,1} \\ y_{1,0} & y_{2,0} & y_{1,1} \\ y_{0,1} & y_{1,1} & y_{0,2} \end{bmatrix} \succeq 0, \\ & 1 - y_{2,0} \geq 0, 1 - y_{0,2} \geq 0, \\ & \exists x \in \mathbb{R}^2 \text{ s.t. } y = (x_1, x_2, x_1^2, x_1 x_2, x_2^2) \end{cases} \quad \xrightarrow{\text{relax}} \quad \begin{cases} \inf_y & y_{2,0} + y_{1,1} + y_{0,2} \\ \text{s.t.} & \begin{bmatrix} 1 & y_{1,0} & y_{0,1} \\ y_{1,0} & y_{2,0} & y_{1,1} \\ y_{0,1} & y_{1,1} & y_{0,2} \end{bmatrix} \succeq 0, \\ & 1 - y_{2,0} \geq 0, 1 - y_{0,2} \geq 0 \end{cases}$$

# The hierarchy of moment relaxations

- The hierarchy of moment relaxations (Lasserre, 2001):

$$\theta_r := \begin{cases} \inf_{\mathbf{y}} & L_{\mathbf{y}}(f) \\ \text{s.t.} & \mathbf{M}_r(\mathbf{y}) \succeq 0, \\ & \mathbf{M}_{r-d_i}(g_i \mathbf{y}) \succeq 0, \quad i = 1, \dots, m, \\ & y_0 = 1. \end{cases}$$

## Example (dual SOS relaxation)

$$\begin{cases} \inf_{\mathbf{x}} & x_1^2 + x_1x_2 + x_2^2 \\ \text{s.t.} & 1 - x_1^2 \geq 0, 1 - x_2^2 \geq 0 \end{cases} \quad \iff \quad \begin{cases} \sup_{\lambda} & \lambda \\ \text{s.t.} & x_1^2 + x_1x_2 + x_2^2 - \lambda \geq 0, \forall \mathbf{x} \in \mathbb{R}^2 \text{ s.t. } (1 - x_1^2 \geq 0, 1 - x_2^2 \geq 0) \end{cases}$$

strengthen

$$\begin{cases} \sup_{\lambda, \sigma_i} & \lambda \\ \text{s.t.} & x_1^2 + x_1x_2 + x_2^2 - \lambda = \sigma_0 + \sigma_1(1 - x_1^2) + \sigma_2(1 - x_2^2), \\ & \sigma_0, \sigma_1, \sigma_2 \in \text{SOS} \end{cases}$$

# The hierarchy of dual SOS relaxations

- The hierarchy of dual SOS relaxations (Parrilo 2000 & Lasserre 2001):

$$\theta_r^* := \left\{ \begin{array}{ll} \sup_{\lambda, \sigma_i} & \lambda \\ \text{s.t.} & f - \lambda = \sigma_0 + \sum_{i=1}^m \sigma_i g_i, \\ & \sigma_0, \sigma_1, \dots, \sigma_m \in \Sigma(\mathbf{x}), \\ & \deg(\sigma_0) \leq 2r, \deg(\sigma_i g_i) \leq 2r, i = 1, \dots, m. \end{array} \right.$$

# The Moment-SOS/Lasserre's hierarchy

$$\begin{array}{ccc} f_{\min} & & \\ \swarrow & & \searrow \\ \vdots & & \vdots \\ \vee | & & \vee | \\ \text{(Moment relaxation)} & \theta_r \quad “=” \quad \theta_r^* & \text{(dual SOS relaxation)} \\ \vee | & & \vee | \\ \vdots & & \vdots \\ \vee | & & \vee | \\ \theta_{r_{\min}} \quad “=” \quad \theta_{r_{\min}}^* & & \end{array}$$

# Asymptotical convergence and finite convergence

- Under Archimedean's condition ( $\approx$  compactness): there exists  $N > 0$   
s.t.  $N - \|\mathbf{x}\|^2 \in \mathcal{Q}(\mathbf{g})$ 
  - ▶  $\theta_r \nearrow f_{\min}$  and  $\theta_r^* \nearrow f_{\min}$  as  $r \rightarrow \infty$  (Putinar's Positivstellensatz, 1993)
  - ▶ Finite convergence happens generically (Nie, 2014)

# Asymptotical convergence and finite convergence

- Under Archimedean's condition ( $\approx$  compactness): there exists  $N > 0$   
s.t.  $N - \|\mathbf{x}\|^2 \in \mathcal{Q}(\mathbf{g})$ 
  - ▶  $\theta_r \nearrow f_{\min}$  and  $\theta_r^* \nearrow f_{\min}$  as  $r \rightarrow \infty$  (**Putinar's Positivstellensatz, 1993**)
  - ▶ Finite convergence happens generically (Nie, 2014)

# Asymptotical convergence and finite convergence

- Under Archimedean's condition ( $\approx$  compactness): there exists  $N > 0$   
s.t.  $N - \|\mathbf{x}\|^2 \in \mathcal{Q}(\mathbf{g})$ 
  - $\theta_r \nearrow f_{\min}$  and  $\theta_r^* \nearrow f_{\min}$  as  $r \rightarrow \infty$  (**Putinar's Positivstellensatz, 1993**)
  - Finite convergence happens generically (**Nie, 2014**)

# Detecting global optimality

- The moment relaxation achieves global optimality ( $\theta_r = f_{\min}$ ) when one of the following conditions holds:
  - ▶ (flat truncation) For some  $r_0 \leq r' \leq r$ ,  $\text{rank } \mathbf{M}_{r'-r_0}(\mathbf{y}) = \text{rank } \mathbf{M}_{r'}(\mathbf{y})$ 
    - ~~ Extract  $\text{rank } \mathbf{M}_{r'}(\mathbf{y})$  globally optimal solutions
  - ▶  $\text{rank } \mathbf{M}_{r_{\min}}(\mathbf{y}) = 1$ 
    - ~~ Extract one globally optimal solution

# Detecting global optimality

- The moment relaxation achieves global optimality ( $\theta_r = f_{\min}$ ) when one of the following conditions holds:
  - ▶ **(flat truncation)** For some  $r_0 \leq r' \leq r$ ,  $\text{rank } \mathbf{M}_{r'-r_0}(\mathbf{y}) = \text{rank } \mathbf{M}_{r'}(\mathbf{y})$ 
    - ~~ Extract  $\text{rank } \mathbf{M}_{r'}(\mathbf{y})$  globally optimal solutions
  - ▶  $\text{rank } \mathbf{M}_{r_{\min}}(\mathbf{y}) = 1$ 
    - ~~ Extract one globally optimal solution

# Detecting global optimality

- The moment relaxation achieves global optimality ( $\theta_r = f_{\min}$ ) when one of the following conditions holds:
  - ▶ **(flat truncation)** For some  $r_0 \leq r' \leq r$ ,  $\text{rank } \mathbf{M}_{r'-r_0}(\mathbf{y}) = \text{rank } \mathbf{M}_{r'}(\mathbf{y})$ 
    - ~~ Extract  $\text{rank } \mathbf{M}_{r'}(\mathbf{y})$  globally optimal solutions
  - ▶  $\text{rank } \mathbf{M}_{r_{\min}}(\mathbf{y}) = 1$ 
    - ~~ Extract one globally optimal solution

# Extension – polynomial matrix optimization

- Robust polynomial matrix inequality optimization:

$$\begin{cases} \inf_{\mathbf{y} \in Y} & f(\mathbf{y}) \\ \text{s.t.} & P(\mathbf{y}, \mathbf{x}) \succeq 0, \quad \forall \mathbf{x} \in X. \end{cases}$$

~~ robust polynomial semidefinite programming

[Guo & Wang, 2023]

# Extension – polynomial dynamic system

- Polynomial dynamic system:

$$\begin{cases} \dot{x}_1 = f_1(\mathbf{x}), \\ \dot{x}_2 = f_2(\mathbf{x}), \\ \vdots \\ \dot{x}_n = f_n(\mathbf{x}), \end{cases}$$

~~ maximal invariant set, attraction region, global attractor, reachable set

## Extension – complex polynomial optimization

- Complex polynomial optimization problem (CPOP):

$$\begin{cases} \inf_{\mathbf{z} \in \mathbb{C}^n} & f(\mathbf{z}, \bar{\mathbf{z}}) \\ \text{s.t.} & g_i(\mathbf{z}, \bar{\mathbf{z}}) \geq 0, \quad i = 1, \dots, m, \\ & h_j(\mathbf{z}, \bar{\mathbf{z}}) = 0, \quad j = 1, \dots, l. \end{cases}$$

~~~ optimal power flow

## Extension – trigonometric polynomial optimization

- Trigonometric polynomial optimization problem:

$$\begin{cases} \inf_{x \in [0, 2\pi]^n} f(\sin x_1, \dots, \sin x_n, \cos x_1, \dots, \cos x_n) \\ \text{s.t. } g_i(\sin x_1, \dots, \sin x_n, \cos x_1, \dots, \cos x_n) \geq 0, \quad i = 1, \dots, m, \\ \quad h_j(\sin x_1, \dots, \sin x_n, \cos x_1, \dots, \cos x_n) = 0, \quad j = 1, \dots, l. \end{cases}$$

~~ signal processing

# Extension – noncommutative polynomial optimization

- Eigenvalue optimization problem:

$$\begin{cases} \inf_X \quad \text{eig } f(X) = f(X_1, \dots, X_n) \\ \text{s.t.} \quad g_i(X) \geq 0, \quad i = 1, \dots, m, \\ \quad \quad \quad h_j(X) = 0, \quad j = 1, \dots, l. \end{cases}$$

~~~ linear Bell inequality

# Extension – noncommutative polynomial optimization

- Trace optimization problem:

$$\begin{cases} \inf_X \text{tr } f(X) = f(X_1, \dots, X_n) \\ \text{s.t. } g_i(X) \geq 0, \quad i = 1, \dots, m, \\ \quad h_j(X) = 0, \quad j = 1, \dots, l. \end{cases}$$

~~ Connes' embedding conjecture

## Extension – trace/state polynomial optimization

- trace polynomial:  $\text{tr}(x_1^2)x_2x_1 + \text{tr}(x_1)\text{tr}(x_2x_1x_2)$ ,  $x_1, \dots, x_n \in \mathcal{B}(\mathcal{H})$
  - state polynomial:  $\varsigma(x_1^2)x_2x_1 + \varsigma(x_1)\varsigma(x_2x_1x_2)$ ,  $x_1, \dots, x_n \in \mathcal{B}(\mathcal{H})$ ,  $\varsigma$  is a formal state (i.e., a positive unital linear functional) on  $\mathcal{B}(\mathcal{H})$
- $\rightsquigarrow$  nonlinear Bell inequality

# More extensions and applications

- The Generalized Moment Problem (GMP)
- Tensor computation/optimization
- Optimal control
- Volume computation of semialgebraic sets
- Computing joint spectral radius
- Polynomial PDE
- ...

# The scalability issue of the Moment-SOS hierarchy

- The size of SDP corresponding to the  $r$ -th SOS relaxation:
  - ➊ PSD constraint:  $\binom{n+r}{r}$
  - ➋ #equality constraint:  $\binom{n+2r}{2r}$
- $r = 2, n < 30$  (Mosek)
- Exploiting structures:
  - ▶ POP
  - ▶ SDP

# The scalability issue of the Moment-SOS hierarchy

- The size of SDP corresponding to the  $r$ -th SOS relaxation:
  - ➊ PSD constraint:  $\binom{n+r}{r}$
  - ➋ #equality constraint:  $\binom{n+2r}{2r}$
- $r = 2, n < 30$  (Mosek)
- Exploiting structures:
  - ▶ POP
  - ▶ SDP

# The scalability issue of the Moment-SOS hierarchy

- The size of SDP corresponding to the  $r$ -th SOS relaxation:
  - ➊ PSD constraint:  $\binom{n+r}{r}$
  - ➋ #equality constraint:  $\binom{n+2r}{2r}$
- $r = 2, n < 30$  (Mosek)
- Exploiting structures:
  - ▶ POP
  - ▶ SDP

# Quotient ring

- Equality constraints:  $h_j(\mathbf{x}) = 0, \quad j = 1, \dots, l$
- Construct the Moment-SOS hierarchy on the quotient ring

$$\mathbb{R}[\mathbf{x}] / (h_1(\mathbf{x}), \dots, h_l(\mathbf{x}))$$

~~~ Gröbner basis

# Quotient ring

- Equality constraints:  $h_j(\mathbf{x}) = 0, \quad j = 1, \dots, l$
- Construct the Moment-SOS hierarchy on the quotient ring

$$\mathbb{R}[\mathbf{x}] / (h_1(\mathbf{x}), \dots, h_l(\mathbf{x}))$$

$\rightsquigarrow$  Gröbner basis

# Symmetry

- **permutation symmetry:**  $(x_1, \dots, x_n) \rightarrow (x_{\tau(1)}, \dots, x_{\tau(n)})$
- **translation symmetry:**  $(x_1, \dots, x_n) \rightarrow (x_{1+i}, \dots, x_{n+i}), x_{n+i} = x_i$
- **sign symmetry:**  $(x_1, \dots, x_n) \rightarrow (-x_1, \dots, -x_n)$
- **conjugate symmetry:**  $z \rightarrow \bar{z}$
- **$\mathbb{T}$ -symmetry:**  $z \rightarrow e^{i\theta} z$

# The procedure for exploiting symmetry

- ① Determine the symmetry group of the POP
- ② Compute the irreducible representations of the symmetry group
- ③ Compute the basis for each isotypic component
- ④ Construct the block diagonal moment-SOS hierarchy

## Smaller monomial basis

When the POP is sparse, possible to use a smaller monomial basis.

Choose

$$\mathcal{B}_r \subsetneq [\mathbf{x}]_r = \{1, x_1, \dots, x_n, x_1^r, \dots, x_n^r\}$$

such that

$$\left( \text{supp}(f) \cup \bigcup_{i=1}^m \text{supp}(g_i) \right) \subseteq \mathcal{B}_r \cdot \mathcal{B}_r$$

For instance, consider the Newton polytope if unconstrained

## Smaller monomial basis

When the POP is sparse, possible to use a smaller monomial basis.

Choose

$$\mathcal{B}_r \subsetneq [\mathbf{x}]_r = \{1, x_1, \dots, x_n, x_1^r, \dots, x_n^r\}$$

such that

$$\left( \text{supp}(f) \cup \bigcup_{i=1}^m \text{supp}(g_i) \right) \subseteq \mathcal{B}_r \cdot \mathcal{B}_r$$

For instance, consider the Newton polytope if unconstrained

# Correlative sparsity

- Correlative sparsity pattern graph  $G^{\text{csp}}(V, E)$ :
  - ▶  $V := \{x_1, \dots, x_n\}$
  - ▶  $\{x_i, x_j\} \in E \iff x_i, x_j \text{ appear in the same term of } f \text{ or in the same constraint polynomial } g_k$
- For each maximal clique of  $G^{\text{csp}}(V, E)$ , do

$$I_k \longmapsto \mathbf{M}_r(\mathbf{y}, I_k), \mathbf{M}_{r-d_i}(g_i \mathbf{y}, I_k)$$

[Waki et al., 2006]

# Correlative sparsity

- Correlative sparsity pattern graph  $G^{\text{csp}}(V, E)$ :
  - ▶  $V := \{x_1, \dots, x_n\}$
  - ▶  $\{x_i, x_j\} \in E \iff x_i, x_j \text{ appear in the same term of } f \text{ or in the same constraint polynomial } g_k$
- For each maximal clique of  $G^{\text{csp}}(V, E)$ , do

$$I_k \longmapsto \mathbf{M}_r(\mathbf{y}, I_k), \mathbf{M}_{r-d_i}(g_i \mathbf{y}, I_k)$$

[Waki et al., 2006]

# Term sparsity

- Term sparsity pattern graph  $G^{\text{tsp}}(V, E)$ :

- $V := [\mathbf{x}]_r = \{1, x_1, \dots, x_n, x_1^r, \dots, x_n^r\}$
- $\{\mathbf{x}^\alpha, \mathbf{x}^\beta\} \in E \iff \mathbf{x}^\alpha \cdot \mathbf{x}^\beta = \mathbf{x}^{\alpha+\beta} \in \text{supp}(f) \cup \bigcup_{i=1}^m \text{supp}(g_i) \cup [\mathbf{x}]_r^2$

$$\begin{matrix} & \cdots & \alpha & \cdots \\ \vdots & \left[ \begin{array}{ccc} & \vdots & \\ \cdots & y_{\alpha+\beta} & \cdots \\ & \vdots & \end{array} \right] \\ \beta & & & \\ \vdots & & & \end{matrix} = \mathbf{M}_r(\mathbf{y})$$

[Wang & Magron & Lasserre, 2021]

# Correlative-term sparsity

- ① Decompose the whole set of variables into cliques by exploiting correlative sparsity
- ② Exploit term sparsity for each subsystem

## Correlative-term sparsity

- ① Decompose the whole set of variables into cliques by exploiting correlative sparsity
- ② Exploit term sparsity for each subsystem

# Problems to investigate

- ① How to exploit different structures simultaneously when the POP possesses multiple structures?
- ② How to detect global optimality and extract optimal solutions in the presence of different structures?

# Problems to investigate

- ① How to exploit different structures simultaneously when the POP possesses multiple structures?
- ② How to detect global optimality and extract optimal solutions in the presence of different structures?

# Global optimality conditions for CPOPs

$$\text{rank } \mathbf{M}_t(\mathbf{y}) = \text{rank } \mathbf{M}_{t-d_K}(\mathbf{y})$$

+

$$\begin{bmatrix} \mathbf{M}_{t-d_K}(\mathbf{y}) & \mathbf{M}_{t-d_K}(\bar{z}_i \mathbf{y}) \\ \mathbf{M}_{t-d_K}(z_i \mathbf{y}) & \mathbf{M}_{t-d_K}(|z_i|^2 \mathbf{y}) \end{bmatrix} \succeq 0, \quad \forall i$$

⇓

global optimality

# Global optimality conditions under conjugate symmetry

conjugate symmetry

+

$$\text{rank } \mathbf{M}_t(\mathbf{y}) = \text{rank } \mathbf{M}_{t-d_K}(\mathbf{y}) = 2$$

⇓

global optimality

[Wang & Magron, 2023]

# Structures of the SOS problem

- Orthogonality:  $\langle A_i, A_j \rangle = 0, \quad \forall i \neq j$
- Sparsity:  $A_i, B_i$  are very sparse

$$\left\{ \begin{array}{ll} \sup_{X_1, X_2, x} & c^T x \\ \text{s.t.} & \langle A_i, X_1 \rangle + \langle B_i, X_2 \rangle + C_i x = b_i, \quad i = 1, \dots, m \\ & X_1, X_2 \succeq 0 \end{array} \right.$$

# Structures of the moment problem

- Low-rank:  $\text{rank}(X^{\text{opt}}) \ll n$
- Unit diagonal:  $\text{diag}(X) = \mathbf{1}$
- Unit trace:  $\text{tr}(X) = 1$

$$\begin{cases} \inf_{X \in \mathbb{R}^{n \times n}} & \langle C, X \rangle \\ \text{s.t.} & \langle A_i, X \rangle = b_i, \quad i = 1, \dots, m \\ & X \succeq 0 \end{cases}$$

$\rightsquigarrow$  manifold structure

[Wang & Hu, 2023]

# Structures of the moment problem


- Low-rank:  $\text{rank}(X^{\text{opt}}) \ll n$
- Unit diagonal:  $\text{diag}(X) = \mathbf{1}$
- Unit trace:  $\text{tr}(X) = 1$

$$\begin{cases} \inf_{X \in \mathbb{R}^{n \times n}} & \langle C, X \rangle \\ \text{s.t.} & \langle A_i, X \rangle = b_i, \quad i = 1, \dots, m \\ & X \succeq 0 \end{cases}$$

$\rightsquigarrow$  manifold structure

[Wang & Hu, 2023]

# Solving large-scale polynomial optimization



# Software

- **TSSOS**: based on JuMP, user-friendly, support commutative/complex/noncommutative polynomial optimization

**<https://github.com/wangjie212/TSSOS>**

- **ManiSDP**: efficiently solve low-rank SDPs via manifold optimization

**<https://github.com/wangjie212/ManiSDP>**

# Binary quadratic programs

表: Random binary quadratic programs  $\min_{\mathbf{x} \in \{-1,1\}^n} \mathbf{x}^\top Q \mathbf{x}$ ,  $r = 2^1$

| n   | n <sub>sdp</sub> | m <sub>sdp</sub> | MOSEK 10.0       |      | SDPNAL+          |      | STRIDE           |      | ManiSDP          |              |
|-----|------------------|------------------|------------------|------|------------------|------|------------------|------|------------------|--------------|
|     |                  |                  | η <sub>max</sub> | time         |
| 10  | 56               | 1,256            | 4.4e-11          | 0.71 | 1.9e-09          | 0.65 | 4.7e-13          | 0.79 | 3.2e-15          | <b>0.14</b>  |
| 20  | 211              | 16,361           | 2.7e-11          | 49.0 | 3.0e-09          | 28.8 | 7.4e-13          | 6.12 | 1.2e-14          | <b>0.53</b>  |
| 30  | 466              | 77,316           | -                | -    | 1.7e-04          | 187  | 1.2e-12          | 65.4 | 2.4e-14          | <b>3.25</b>  |
| 40  | 821              | 236,121          | -                | -    | 2.1e-08          | 813  | 4.4e-13          | 249  | 4.1e-14          | <b>10.5</b>  |
| 50  | 1,276            | 564,776          | -                | -    | 1.6e-07          | 3058 | 7.8e-09          | 826  | 6.4e-14          | <b>31.1</b>  |
| 60  | 1,831            | 1,155,281        | -                | -    | *                | *    | 1.3e-12          | 2118 | 7.9e-14          | <b>94.3</b>  |
| 120 | 7,261            | 17,869,161       | -                | -    | -                | -    | -                | -    | 3.5e-13          | <b>30801</b> |

[Wang & Hu, 2023]

<sup>1</sup>-: out of memory, \*: >10000s

# The robust rotation search problem

- $q$ : unit quaternion parametrization of a 3D rotation
- $(z_i \in \mathbb{R}^3, w_i \in \mathbb{R}^3)_{i=1}^N$ :  $N$  pairs of 3D points
- $\tilde{z} := [z^\top, 0]^\top \in \mathbb{R}^4$
- $\tilde{w} := [w^\top, 0]^\top \in \mathbb{R}^4$
- $\beta_i$ : threshold determining the maximum inlier residual

$$\min_{\|q\|=1} \sum_{i=1}^N \min \left\{ \frac{\|\tilde{z}_i - q \circ \tilde{w}_i \circ q^{-1}\|^2}{\beta_i^2}, 1 \right\}$$

# The robust rotation search problem

表: Results for the robust rotation search problem,  $r = 2$

| N   | MOSEK 10.0    |      | SDPLR 1.03    |      | SDPNAL+       |      | STRIDE        |      | ManiSDP       |             |
|-----|---------------|------|---------------|------|---------------|------|---------------|------|---------------|-------------|
|     | $\eta_{\max}$ | time        |
| 50  | 4.7e-10       | 16.4 | 9.8e-03       | 12.5 | 1.1e-02       | 106  | 2.8e-09       | 18.3 | 6.6e-09       | <b>3.02</b> |
| 100 | 2.0e-11       | 622  | 3.6e-04       | 106  | 7.1e-02       | 642  | 3.1e-09       | 73.0 | 1.0e-09       | <b>22.9</b> |
| 150 | -             | -    | 2.0e-03       | 291  | 8.0e-02       | 1691 | 4.3e-11       | 249  | 1.6e-09       | <b>33.5</b> |
| 200 | -             | -    | 3.1e-02       | 459  | 8.3e-02       | 2799 | 1.4e-09       | 254  | 6.3e-10       | <b>65.3</b> |
| 300 | -             | -    | 1.1e-03       | 1264 | 5.2e-02       | 3528 | 4.1e-10       | 1176 | 1.1e-09       | <b>188</b>  |
| 500 | -             | -    | *             | *    | *             | *    | 7.1e-09       | 5627 | 5.2e-10       | <b>601</b>  |

[Wang & Hu, 2023]

# The AC-OPF problem

$$\left\{ \begin{array}{l} \inf_{V_i, S_k^g \in \mathbb{C}} \quad \sum_{k \in G} (\mathbf{c}_{2k} \Re(S_k^g)^2 + \mathbf{c}_{1k} \Re(S_k^g) + \mathbf{c}_{0k}) \\ \text{s.t.} \quad \angle V_r = 0, \\ \mathbf{S}_k^{gl} \leq S_k^g \leq \mathbf{S}_k^{gu}, \quad \forall k \in G, \\ \mathbf{v}_i^l \leq |V_i| \leq \mathbf{v}_i^u, \quad \forall i \in N, \\ \sum_{k \in G_i} S_k^g - \mathbf{S}_i^d - \mathbf{Y}_i^s |V_i|^2 = \sum_{(i,j) \in E_i \cup E_i^R} S_{ij}, \quad \forall i \in N, \\ S_{ij} = (\bar{\mathbf{Y}}_{ij} - \mathbf{i} \frac{\mathbf{b}_{ij}^c}{|\mathbf{T}_{ij}|^2}) \frac{|\mathbf{V}_i|^2}{|\mathbf{T}_{ij}|^2} - \bar{\mathbf{Y}}_{ij} \frac{\mathbf{V}_i \bar{\mathbf{V}}_j}{\mathbf{T}_{ij}}, \quad \forall (i,j) \in E, \\ S_{ji} = (\bar{\mathbf{Y}}_{ij} - \mathbf{i} \frac{\mathbf{b}_{ij}^c}{2}) |\mathbf{V}_j|^2 - \bar{\mathbf{Y}}_{ij} \frac{\bar{\mathbf{V}}_i \mathbf{V}_j}{\mathbf{T}_{ij}}, \quad \forall (i,j) \in E, \\ |S_{ij}| \leq \mathbf{s}_{ij}^u, \quad \forall (i,j) \in E \cup E^R, \\ \theta_{ij}^{\Delta l} \leq \angle(V_i \bar{V}_j) \leq \theta_{ij}^{\Delta u}, \quad \forall (i,j) \in E. \end{array} \right.$$

# The AC-OPF problem

| n    | m     | CS ( $r = 2$ )   |          |      |       | CS+TS ( $r = 2$ ) |          |      |       |
|------|-------|------------------|----------|------|-------|-------------------|----------|------|-------|
|      |       | $n_{\text{sdp}}$ | opt      | time | gap   | $n_{\text{sdp}}$  | opt      | time | gap   |
| 12   | 28    | 28               | 1.1242e4 | 0.21 | 0.00% | 22                | 1.1242e4 | 0.09 | 0.00% |
| 20   | 55    | 28               | 1.7543e4 | 0.56 | 0.05% | 22                | 1.7543e4 | 0.30 | 0.05% |
| 72   | 297   | 45               | 4.9927e3 | 4.43 | 0.07% | 22                | 4.9920e3 | 2.69 | 0.08% |
| 114  | 315   | 120              | 7.6943e4 | 94.9 | 0.00% | 39                | 7.6942e4 | 14.8 | 0.00% |
| 344  | 1325  | 253              | -        | -    | -     | 73                | 1.0470e5 | 169  | 0.50% |
| 348  | 1809  | 253              | -        | -    | -     | 34                | 1.2096e5 | 201  | 0.03% |
| 766  | 3322  | 153              | 3.3072e6 | 585  | 0.68% | 44                | 3.3042e6 | 33.9 | 0.77% |
| 1112 | 4613  | 496              | -        | -    | -     | 31                | 7.2396e4 | 410  | 0.25% |
| 4356 | 18257 | 378              | -        | -    | -     | 27                | 1.3953e6 | 934  | 0.51% |
| 6698 | 29283 | 1326             | -        | -    | -     | 76                | 5.9858e5 | 1886 | 0.47% |

[Wang & Magron & Lasserre, 2022]

# Nonlinear Bell inequality

- $\lambda(A_1B_2 + A_2B_1)^2 + \lambda(A_1B_1 - A_2B_2)^2 \leq 4$

$$\begin{cases} \sup_{x_i, y_j} & (\varsigma(x_1y_2) + \varsigma(x_2y_1))^2 + (\varsigma(x_1y_1) - \varsigma(x_2y_2))^2 \\ \text{s.t.} & x_i^2 = 1, y_j^2 = 1, [x_i, y_j] = 0 \text{ for } i, j = 1, 2. \end{cases}$$

- For classical models: 4
- For quantum commuting model: 4 ( $r = 3$ )

[Igor et al., 2023]

# Nonlinear Bell inequality

- $\lambda(A_1B_2 + A_2B_1)^2 + \lambda(A_1B_1 - A_2B_2)^2 \leq 4$

$$\begin{cases} \sup_{x_i, y_j} & (\varsigma(x_1y_2) + \varsigma(x_2y_1))^2 + (\varsigma(x_1y_1) - \varsigma(x_2y_2))^2 \\ \text{s.t.} & x_i^2 = 1, y_j^2 = 1, [x_i, y_j] = 0 \text{ for } i, j = 1, 2. \end{cases}$$

- For classical models: 4
- For quantum commuting model: 4 ( $r = 3$ )

[Igor et al., 2023]

# Nonlinear Bell inequality

- $\lambda(A_2 + B_1 + B_2 - A_1B_1 + A_2B_1 + A_1B_2 + A_2B_2) - \lambda(A_1)\lambda(B_1) - \lambda(A_2)\lambda(B_1) - \lambda(A_2)\lambda(B_2) - \lambda(A_1)^2 - \lambda(B_2)^2$

$$\left\{ \begin{array}{l} \sup_{x_i, y_j} \varsigma(x_2) + \varsigma(y_1) + \varsigma(y_2) - \varsigma(x_1y_1) + \varsigma(x_2y_1) + \varsigma(x_1y_2) + \varsigma(x_2y_2) \\ \quad - \varsigma(x_1)\varsigma(y_1) - \varsigma(x_2)\varsigma(y_1) - \varsigma(x_2)\varsigma(y_2) - \varsigma(x_1)^2 - \varsigma(y_2)^2 \\ \text{s.t. } x_i^2 = 1, y_j^2 = 1, [x_i, y_j] = 0 \text{ for } i, j = 1, 2. \end{array} \right.$$

- For classical models: 3.375
- For quantum commuting model: 3.5114 ( $r = 2$ )

[Igor et al., 2023]

# Nonlinear Bell inequality

- $\lambda(A_2 + B_1 + B_2 - A_1B_1 + A_2B_1 + A_1B_2 + A_2B_2) - \lambda(A_1)\lambda(B_1) - \lambda(A_2)\lambda(B_1) - \lambda(A_2)\lambda(B_2) - \lambda(A_1)^2 - \lambda(B_2)^2$

$$\left\{ \begin{array}{l} \sup_{x_i, y_j} \quad \varsigma(x_2) + \varsigma(y_1) + \varsigma(y_2) - \varsigma(x_1y_1) + \varsigma(x_2y_1) + \varsigma(x_1y_2) + \varsigma(x_2y_2) \\ \qquad - \varsigma(x_1)\varsigma(y_1) - \varsigma(x_2)\varsigma(y_1) - \varsigma(x_2)\varsigma(y_2) - \varsigma(x_1)^2 - \varsigma(y_2)^2 \\ \text{s.t.} \quad x_i^2 = 1, y_j^2 = 1, [x_i, y_j] = 0 \text{ for } i, j = 1, 2. \end{array} \right.$$

- For classical models: 3.375
- For quantum commuting model: 3.5114 ( $r = 2$ )

[Igor et al., 2023]

# Ground state energy of quantum many-body systems

The **Heisenberg chain** is defined by the Hamiltonian:

$$H = \sum_{i=1}^N \sum_{a \in \{x,y,z\}} \sigma_i^a \sigma_{i+1}^a.$$

The **ground state energy** of the Heisenberg chain equals the optimum of the NCPOP:

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

# Structures of the Heisenberg model

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

- ① sparsity
- ② sign symmetry
- ③ translation symmetry
- ④ permutation symmetry
- ⑤ mirror symmetry

# Structures of the Heisenberg model

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

- ① sparsity
- ② sign symmetry
- ③ translation symmetry
- ④ permutation symmetry
- ⑤ mirror symmetry

# Structures of the Heisenberg model

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

- ① sparsity
- ② sign symmetry
- ③ translation symmetry
- ④ permutation symmetry
- ⑤ mirror symmetry

# Structures of the Heisenberg model

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

- ① sparsity
- ② sign symmetry
- ③ translation symmetry
- ④ permutation symmetry
- ⑤ mirror symmetry

# Structures of the Heisenberg model

$$\left\{ \begin{array}{ll} \min_{\{|\psi\rangle, \sigma_i^a\}} & \langle \psi | H | \psi \rangle \\ \text{s.t.} & (\sigma_i^a)^2 = 1, \quad i = 1, \dots, N, a \in \{x, y, z\}, \\ & \sigma_i^x \sigma_i^y = i \sigma_i^z, \sigma_i^y \sigma_i^z = i \sigma_i^x, \sigma_i^z \sigma_i^x = i \sigma_i^y, \quad i = 1, \dots, N, \\ & \sigma_i^a \sigma_j^b = \sigma_j^b \sigma_i^a, \quad 1 \leq i \neq j \leq N, a, b \in \{x, y, z\}. \end{array} \right.$$

- ① sparsity
- ② sign symmetry
- ③ translation symmetry
- ④ permutation symmetry
- ⑤ mirror symmetry

# Ground state energy of the Heisenberg chain





图: Ground state energy of the Heisenberg chain [Wang et al., 2023]

# Summary



# Conclusions

- Polynomial optimization provides a unified scheme for global optimization of various non-convex problems.
- The scalability of the Moment-SOS hierarchy can be significantly improved by exploiting plenty of algebraic structures.
- There are tons of applications in diverse fields!

# Main references

- **Jie Wang**, Victor Magron and Jean B. Lasserre, *TSSOS: A Moment-SOS hierarchy that exploits term sparsity*, SIAM Journal on Optimization, 2021.
- **Jie Wang**, Victor Magron and Jean B. Lasserre, *Chordal-TSSOS: a moment-SOS hierarchy that exploits term sparsity with chordal extension*, SIAM Journal on Optimization, 2021.
- **Jie Wang** and Victor Magron, Exploiting Sparsity in Complex Polynomial Optimization, Journal of Optimization Theory and Applications, 2021.
- **Jie Wang**, Victor Magron, Jean B. Lasserre and Ngoc H. A. Mai, *CS-TSSOS: Correlative and term sparsity for large-scale polynomial optimization*, ACM Transactions on Mathematical Software, 2022.

# Main references

- **Jie Wang** and Victor Magron, Exploiting Term Sparsity in Noncommutative Polynomial Optimization, Computational Optimization and Applications, 2021.
- Igor Klep, Victor Magron, Jurij Volčič and **Jie Wang**, State Polynomials: Positivity, Optimization and Nonlinear Bell Inequalities, arXiv, 2023.
- **Jie Wang** and Liangbing Hu, Solving Low-Rank Semidefinite Programs via Manifold Optimization, arXiv, 2023.
- Feng Guo and **Jie Wang**, A Moment-SOS Hierarchy for Robust Polynomial Matrix Inequality Optimization with SOS-Convexity, arXiv, 2023.

# A new book



# Thank You!

<https://wangjie212.github.io/jiewang>